

<u>SUBJECT</u>		<u>DATE</u>
1320. Treated Hazardous Waste Used as Dust Suppressant		FEB 28, 2019
1321. Decharacterized RCRA Waste - Manifesting and LDR Reporting	ENCORE	MAR 7, 2019
1322. Decharacterized Hazardous Waste Listed Solely for Non-Toxic Characteristics	ENCORE	MAR 14, 2019
1323. Decharacterized Wastes, ≤90-Day Accumulation Time Limits and LDR Storage Prohibition	ENCORE	MAR 21, 2019
1324. Decharacterized Wastes and the LDR Dilution Prohibition	ENCORE	MAR 28, 2019
1325. PCB Decontamination Standard with No Decontamination Performed	ENCORE	APR 4, 2019
1326. PCB Manifest Relief a.k.a., When is a PCB Manifest Not Required?	ENCORE	APR 11, 2019
1327. PCB Manifest Relief a.k.a., When is a PCB Manifest Not Required? – The Sequel	ENCORE	APR 18, 2019
1328. PCB Concentrations and Micrograms per Centimeters Squared (µg/cm ²)	ENCORE	APR 25, 2019
1329. Operating Record vs. Operating Log	ENCORE	MAY 2, 2019
1330. Operating Records Not Referenced in the “Operating Record” Regulations	ENCORE	MAY 9, 2019
1331. Washington State Used Oil and Mixtures with Other Materials	ENCORE	MAY 16, 2019
1332. Used Oil Filter Regulation – The Feds vs. Washington State	ENCORE	MAY 23, 2019
1333. Printed Circuit Board Recycling – Shredded vs. Whole	ENCORE	MAY 30, 2019
1334. Universal Waste Alkaline Batteries and Self-Transportation	ENCORE	JUN 6, 2019
1335. Universal Waste Lithium Batteries and Self-Transportation	ENCORE	JUN 13, 2019
1336. RCRA Hazard Labeling – A Random Scenario		JUN 20, 2019
1337. Regulatory Status of Chromated, Copper, Arsenate, (CCA) Wood as Wood Mulch	ENCORE	JUN 27, 2019
1338. Unused Paraformaldehyde - U Listed Hazardous Waste or Not?	ENCORE	JUL 3, 2019
1339. The Hazardous Waste Characteristic of Reactivity (D003)	ENCORE	JUL 11, 2019
1340. Central Accumulation Areas and Signage Requirements		JUL 18, 2019
1341. RCRA EPA Identification Numbers – Site Specifics	ENCORE	JUL 25, 2019
1342. RCRA EPA Identification Numbers – Transporters	ENCORE	AUG 1, 2019
1343. Paint Wastes and the Applicability of the F001-F005 Listings to Ingredients	ENCORE	AUG 8, 2019
1344. F Listings and Ingredients in Commercial Chemical Product Formulations	ENCORE	AUG 15, 2019
1345. PCB Containers and ≥50 ppm	ENCORE	AUG 22, 2019
1346. CERCLA Hazardous Substances – The Petroleum Exclusion	ENCORE	AUG 29, 2019
1347. PCB Concentration Assumptions for Use vs. PCB Disposal	ENCORE	SEP 5, 2019
1348. RCRA LR One-Year Storage Prohibition vs., PCB One-Year Disposal Time Limit		SEP 12, 2019
1349. Regulatory Status of PCB Remediation Wastes Disposed Prior to April 18, 1978	ENCORE	SEP 19, 2019
1350. Regulatory Status of PCB Remediation Wastes Disposed Prior to April 18, 1978 – A Follow-Up		SEP 26, 2019
1351. PCB Waste Regulation and April 18, 1978 vs. July 2, 1979		OCT 3, 2019
1352. PCB Waste Storage Limitations and the One-Year Extension	ENCORE	OCT 10, 2019
1353. PCB Waste Storage Limitations and the PCB Radioactive Waste Exemption	ENCORE	OCT 17, 2019
1354. LDR One-Year Storage Prohibition and Generator Permitted Storage	ENCORE	OCT 24, 2019
1355. LDR Notification/Certification and Generator Permitted Storage		OCT 31, 2019
1356. Disposing of PCB Ballasts with PCB Potting Material	ENCORE	NOV 7, 2019

Approved for Public Release;
Further Dissemination Unlimited

DISCLAIMER - “Two Minute Training” (“2MT”) is a peer-to-peer communication, presented to share the benefit of the author’s work experience with other professionals, who can independently evaluate his analysis. 2MT does not necessarily reflect the opinions, conclusions or policies of the author’s past or current employers or the US Department of Energy. The author’s employers do not take any responsibility for the accuracy of its conclusions. 2MT is not intended to be used as authoritative guidance or direction by any person or entity. Anyone transmitting or reproducing it is prohibited from modifying its content, this disclaimer, or other text, or republishing it independent of its original source.

TWO MINUTE TRAINING

TO: CH2M HILL PLATEAU REMEDIATION COMPANY

FROM: PAUL W. MARTIN, RCRA Subject Matter Expert
CHPRC Environmental Protection, Hanford, WA

SUBJECT: DISPOSING OF PCB BALLASTS WITH PCB POTTING MATERIAL

DATE: NOVEMBER 7, 2019

<u>CHPRC Projects</u>	<u>CH PRC - Env. Protection</u>	<u>MSA</u>	<u>Hanford Laboratories</u>	<u>Other Hanford Contractors</u>	<u>Other Hanford Contractors</u>
Richard Austin Tania Bates Rene Catlow Richard Clinton Larry Cole Laura Cusack John Dent Lorna Dittmer Stuart Hildreth Mike Jennings Stephanie Johansen Sasa Kosjerina Melvin Lakes Richard Lipinski Stuart Mortensen Dave Richards Phil Sheely Connie Simiele Jeff Westcott	Jeff Bramson Bob Bullock Frank Carleo Bill Cox Jeanne Elkins Ryan Fischer Jonathan Fullmer Ted Hopkins Barry Lawrence Jim Leary Diane Leist Mitch Marrott Stewart McMahand Brian Mitcheltree Anthony Nagel Linda Petersen Fred Ruck Sean Sexton Dave Shea Ray Swenson Kat Thompson Wayne Toebe Eric Trotta Daniel Turlington Dave Watson	Brett Barnes Michael Carlson Mike Demiter Kip George Jerry Cammann Jeff Ehlis Garin Erickson Panfilo Gonzalez Jr. Dashia Huff Mark Kamberg Jon McKibben Saul Martinez Matt Mills Carly Nelson Michelle Oates Eric Pennala Jon Perry Christina Robison Christian Seavoy David Shaw John Skogle Lana Strickling Greg Sullivan	(TBD) <u>DOE RL, ORP, WIPP</u> Mary Beth Burandt Duane Carter Al Farabee Tony McKarns	Bill Bachmann Dean Baker Scott Baker Lucinda Borneman Paul Crane Tina Crane Ron Del Mar John Dorian Mark Ellefson Darrin Faulk Rob Gregory James Hamilton Andy Hobbs Ryan Johnson Megan Lerchen Mike Lowery Michael Madison Terri Mars Cary Martin Grant McCalmant Steve Metzger Tony Miskho Tom Moon Chuck Mulkey Kirk Peterson	Dan Saueressig Joelle Moss Glen Triner Greg Varljen Julie Waddoups Jay Warwick Ted Wooley

DISCLAIMER - "Two Minute Training" ("2MT") is a peer-to-peer communication, presented to share the benefit of the author's work experience with other professionals, who can independently evaluate his analysis. 2MT does not necessarily reflect the opinions, conclusions or policies of the author's past or current employers or the US Department of Energy. The author's employers do not take any responsibility for the accuracy of its conclusions. 2MT is not intended to be used as authoritative guidance or direction by any person or entity. Anyone transmitting or reproducing it is prohibited from modifying its content, this disclaimer, or other text, or republishing it independent of its original source.

TWO MINUTE TRAINING

SUBJECT: Disposing of PCB Ballasts with PCB Potting Material

Q: A customer has a drum of waste fluorescent lamp ballasts containing intact and non-leaking PCB small capacitors surrounded by an insulating material known as potting material. The PCB concentrations of the potting material vary from <50 ppm to ≥50 ppm PCBs. What are the disposal options for these PCB fluorescent ballasts?

A: Per the USEPA, "[PCB Question and Answer Manual, June 2014](#)", page 45, question 1:

"This depends on the concentration of PCBs in the potting material and whether the ballast contains an intact or non-intact PCB small capacitor. If the PCB concentration of the potting material is <50 ppm and the ballast contains either no PCB small capacitor or an intact and non-leaking PCB small capacitor, you can dispose of the ballast as municipal solid waste (see [§761.60\(b\)\(2\)\(ii\)](#)). If the PCB concentration of the potting material is ≥ 50 ppm and the ballast contains either no PCB small capacitor or an intact and non-leaking PCB small capacitor, you can dispose of the ballast as PCB bulk product waste in a TSCA incinerator, a TSCA/RCRA landfill, a facility permitted, licensed, or registered by a state as a municipal or non-municipal non-hazardous waste landfill, or by means of an approved destruction method, decontamination, or risk-based disposal method (see [§761.62](#)). Regardless of the PCB concentration of the potting material, you must dispose of ballasts containing non-intact or leaking capacitors as PCB bulk product waste in accordance with [§761.62\(a\)](#) or (c)."

In other words:

- If the PCB small capacitor is intact/non-leaking and the potting material is <50 ppm – dispose in municipal landfill.
- If the PCB small capacitor is intact/non-leaking and potting material is ≥50 ppm – dispose in either a TSCA incinerator, a TSCA/RCRA landfill, a state permitted municipal or non-municipal nonhazardous landfill (leach testing per 761.62(b) required), or an approved destruction, decontamination, or a risk-based disposal method.
- If the PCB small capacitor is not intact and is leaking, regardless of PCB concentration in the potting material – dispose either in a TSCA incinerator, a TSCA/RCRA landfill, or by an approved destruction method, or decontamination, or a risk-based disposal method, but NOT in a state permitted municipal or non-municipal nonhazardous landfill.

Since the customer's fluorescent ballasts contain intact/non-leaking PCB small capacitors with potting material PCB concentrations ≥ 50 PPM, at a minimum these ballasts could be disposed in a state permitted municipal landfill provided that leach testing per 40 CFR 761.62(b)(1)(ii) is conducted and the ballasts leach <10 µg/L of water. Other disposal options are TSCA incineration, TSCA/RCRA landfilling or some other approved destruction or decontamination method.

SUMMARY:

- Intact/non-leaking PCB small capacitors with PCB potting material <50 ppm can be disposed in municipal landfills.
- Intact/non-leaking PCB small capacitors with potting material ≥50 ppm PCBs can be disposed in a TSCA incinerator, a TSCA/RCRA landfill, a state permitted municipal/non-municipal nonhazardous waste landfill, or via an approved destruction method, or decontamination, or a risk-based disposal method.
- Non-intact and leaking PCB small capacitors, regardless of the PCB concentration in the potting material can be disposed either in a TSCA incinerator, a TSCA/RCRA landfill, or by an approved destruction method, or decontamination, or a risk-based disposal method, but NOT in a state permitted municipal (etc.) landfill.

Voluminous excerpts from [40 CFR 761.3](#), [761.50](#), [761.60](#) and [761.62](#) are attached to the e-mail. If you have any questions, please contact me at Paul_W_Martin@rl.gov or at (509) 376-6620.

FROM: Paul W. Martin

DATE: 11/07/19

FILE: 2MT\2019\110719.rtf

PG: 1

DISCLAIMER - "Two Minute Training" ("2MT") is a peer-to-peer communication, presented to share the benefit of the author's work experience with other professionals, who can independently evaluate his analysis. 2MT does not necessarily reflect the opinions, conclusions or policies of the author's past or current employers or the US Department of Energy. The author's employers do not take any responsibility for the accuracy of its conclusions. 2MT is not intended to be used as authoritative guidance or direction by any person or entity. Anyone transmitting or reproducing it is prohibited from modifying its content, this disclaimer, or other text, or republishing it independent of its original source.

TWO MINUTE TRAINING – ATTACHMENT

SUBJECT: Disposing of PCB Ballasts with PCB Potting Material

40 CFR Part 761.3 Definitions

For the purpose of this part:

Fluorescent light ballast means a device that electrically controls fluorescent light fixtures and that includes a capacitor containing 0.1 kg or less of dielectric.

PCB bulk product waste means waste derived from manufactured products containing PCBs in a non-liquid state, at any concentration where the concentration at the time of designation for disposal was ≥ 50 ppm PCBs. PCB bulk product waste does not include PCBs or PCB Items regulated for disposal under §761.60(a) through (c), §761.61, §761.63, or §761.64. PCB bulk product waste includes, but is not limited to:

- (1) Non-liquid bulk wastes or debris from the demolition of buildings and other man-made structures manufactured, coated, or serviced with PCBs. PCB bulk product waste does not include debris from the demolition of buildings or other man-made structures that is contaminated by spills from regulated PCBs which have not been disposed of, decontaminated, or otherwise cleaned up in accordance with subpart D of this part.
- (2) PCB-containing wastes from the shredding of automobiles, household appliances, or industrial appliances.
- (3) Plastics (such as plastic insulation from wire or cable; radio, television and computer casings; vehicle parts; or furniture laminates); preformed or molded rubber parts and components; applied dried paints, varnishes, waxes or other similar coatings or sealants; caulking; adhesives; paper; Galbestos; sound deadening or other types of insulation; and felt or fabric products such as gaskets.
- (4) Fluorescent light ballasts containing PCBs in the potting material.

PCB Equipment means any manufactured item, other than a PCB Container or a PCB Article Container, which contains a PCB Article or other PCB Equipment, and includes microwave ovens, electronic equipment, and fluorescent light ballasts and fixtures.

40 CFR 761.50(b)(2)(i)

Fluorescent light ballasts containing PCBs only in an intact and non-leaking PCB Small Capacitor are regulated for disposal under §761.60(b)(2)(ii).

40 CFR 761.50(b)(2)(ii)

Fluorescent light ballasts containing PCBs in the potting material are regulated for disposal as PCB bulk product waste under §761.62.

40 CFR 761.60 Disposal requirements

(b)(2)(ii) Any person may dispose of PCB Small Capacitors as municipal solid waste, unless that person is subject to the requirements of paragraph (b)(2)(iv) of this section.

(b)(6)(iii) Fluorescent light ballasts containing PCBs in their potting material must be disposed of in a TSCA-approved disposal facility, as bulk product waste under §761.62, as household waste under §761.63 (where applicable), or in accordance with the decontamination provisions of §761.79.

FROM: Paul W. Martin

DATE: 11/07/19

FILE: 2MT\2019\110719.rtf

PG: 2

DISCLAIMER - "Two Minute Training" ("2MT") is a peer-to-peer communication, presented to share the benefit of the author's work experience with other professionals, who can independently evaluate his analysis. 2MT does not necessarily reflect the opinions, conclusions or policies of the author's past or current employers or the US Department of Energy. The author's employers do not take any responsibility for the accuracy of its conclusions. 2MT is not intended to be used as authoritative guidance or direction by any person or entity. Anyone transmitting or reproducing it is prohibited from modifying its content, this disclaimer, or other text, or republishing it independent of its original source.

TWO MINUTE TRAINING – ATTACHMENT

SUBJECT: Disposing of PCB Ballasts with PCB Potting Material

40 CFR 761.62 Disposal of PCB bulk product waste

PCB bulk product waste shall be disposed of in accordance with paragraph (a), (b), or (c) of this section. Under some of these provisions, it may not be necessary to determine the PCB concentration or leaching characteristics of the PCB bulk product waste. When it is necessary to analyze the waste to make either of these determinations, use the applicable procedures in subpart R of this part to sample the waste for analysis, unless EPA approves another sampling plan under paragraph (c) of this section.

(a) *Performance-based disposal.* Any person disposing of PCB bulk product waste may do so as follows:

- (1) In an incinerator approved under §761.70.
- (2) In a chemical waste landfill approved under §761.75.
- (3) In a hazardous waste landfill permitted by EPA under section 3004 of RCRA, or by a State authorized under section 3006 of RCRA.
- (4) Under an alternate disposal approval under §761.60(e).
- (5) In accordance with the decontamination provisions of §761.79.
- (6) For metal surfaces in contact with PCBs, in accordance with the thermal decontamination provisions of §761.79(c)(6).
- (7) In accordance with a TSCA PCB Coordinated Approval issued under §761.77.

(b) *Disposal in solid waste landfills.*

(1) Any person may dispose of the following PCB bulk product waste in a facility permitted, licensed, or registered by a State as a municipal or non-municipal non-hazardous waste landfill:

(i) Plastics (such as plastic insulation from wire or cable; radio, television and computer casings; vehicle parts; or furniture laminates); preformed or molded rubber parts and components; applied dried paints, varnishes, waxes or other similar coatings or sealants; caulking; Galbestos; non-liquid building demolition debris; or non-liquid PCB bulk product waste from the shredding of automobiles or household appliances from which PCB small capacitors have been removed (shredder fluff).

(ii) Other PCB bulk product waste, sampled in accordance with the protocols set out in subpart R of this part, that leaches PCBs at <10 µg/L of water measured using a procedure used to simulate leachate generation.

(2) Any person may dispose of PCB bulk product waste other than those materials meeting the conditions of paragraph (b)(1) of this section, (e.g., paper or felt gaskets contaminated by liquid PCBs in a facility that is permitted, licensed, or registered by a State to manage municipal solid waste subject to part 258 of this chapter or non-municipal non-hazardous waste subject to §§257.5 through 257.30 of this chapter, as applicable, if:

(i) The PCB bulk product waste is segregated from organic liquids disposed of in the landfill unit.

(ii) Leachate is collected from the landfill unit and monitored for PCBs.

(3) Any release of PCBs (including but not limited to leachate) from the landfill unit shall be cleaned up in accordance with §761.61.

TWO MINUTE TRAINING – ATTACHMENT

SUBJECT: Disposing of PCB Ballasts with PCB Potting Material

40 CFR 761.62 Disposal of PCB bulk product waste. *(Continued)*

(4)

(i) Any person disposing off-site of PCB bulk product waste regulated under paragraph (b)(1) of this section at a waste management facility not having a commercial PCB storage or disposal approval must provide written notice to the facility a minimum of 15 days in advance of the first shipment from the same disposal waste stream. The notice shall state that the PCB bulk product waste may include components containing PCBs at ≥ 50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCBs at those levels, and that the PCB bulk product waste is known or presumed to leach < 10 $\mu\text{g/L}$ PCBs.

(ii) Any person disposing off-site of PCB bulk product waste regulated under paragraph (b)(2) of this section at a waste management facility not having a commercial PCB storage or disposal approval must provide written notice to the facility a minimum of 15 days in advance of the first shipment from the same disposal waste stream and with each shipment thereafter. The notice shall state that the PCB bulk product waste may include components containing PCBs at ≥ 50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCBs at those levels, and that the PCB bulk product waste is known or presumed to leach ≥ 10 $\mu\text{g/L}$ PCBs.

(5) Any person disposing of PCB bulk product waste must maintain a written record of all sampling and analysis of PCBs or notifications made under this paragraph for 3 years from the date of the waste's generation. The records must be made available to EPA upon request.

(6) Requirements in subparts C, J, and K of this part do not apply to waste disposed of under paragraph (b) of this section.

(c) *Risk-based disposal approval.*

(1) Any person wishing to sample or dispose of PCB bulk product waste in a manner other than prescribed in paragraphs (a) or (b) of this section, or store PCB bulk product waste in a manner other than prescribed in §761.65, must apply in writing to the Regional Administrator in the Region where the sampling, disposal, or storage site is located, for sampling, disposal, or storage occurring in a single EPA Region; or to the Director, Office of Resource Conservation and Recovery, for sampling, disposal, or storage occurring in more than one EPA Region. Each application must contain information indicating that, based on technical, environmental, or waste-specific characteristics or considerations, the proposed sampling, disposal, or storage methods or locations will not pose an unreasonable risk or injury to health or the environment. EPA may request other information that it believes necessary to evaluate the application. No person may conduct sampling, disposal, or storage activities under this paragraph prior to obtaining written approval by EPA.

(2) EPA will issue a written decision on each application for a risk-based sampling, disposal, or storage method for PCB bulk product wastes. EPA will approve such an application if it finds that the method will not pose an unreasonable risk of injury to health or the environment.

EPA Region III Comment

"The small capacitor exemption from the existing disposal requirements for PCB wastes does not apply under two circumstances. Under existing regulations, if a PCB Small Capacitor is leaking, it is regulated for disposal as a PCB Article and must be disposed of as a PCB waste. If the "Potting Material" (the insulating material inside the ballast) contains PCBs at concentrations greater than or equal to 50 ppm, then the PCB ballast is a PCB Article and the entire PCB ballast is regulated for disposal as PCB waste, even if the internal small capacitor remains intact and non-leaking."

FROM: Paul W. Martin

DATE: 11/07/19

FILE: 2MT\2019\110719.rtf

PG: 4

DISCLAIMER - "Two Minute Training" ("2MT") is a peer-to-peer communication, presented to share the benefit of the author's work experience with other professionals, who can independently evaluate his analysis. 2MT does not necessarily reflect the opinions, conclusions or policies of the author's past or current employers or the US Department of Energy. The author's employers do not take any responsibility for the accuracy of its conclusions. 2MT is not intended to be used as authoritative guidance or direction by any person or entity. Anyone transmitting or reproducing it is prohibited from modifying its content, this disclaimer, or other text, or republishing it independent of its original source.